



Technical data



Caution for safety
(Read before installing)



H: Head cover

R: Rod cover


End lock type

Table for standard stroke

Tube I.D.	Stroke (mm)
ø32, 40	25,50,75,100,125,150,200,250,300

Order example


MCMBL — 11 — 40 — 100 — AR — G



⚠ Caution

For (A) Cushion air (Adjustable)

- To adjust a cushion needle, please slowly turn the needle valve from the fully closed status to the required status which needs to be within 2.5 turns.
- If the needle valve loosen excessively, the buffer doesn't take effect and the lifetime of cylinder would be shortened.



Features

- Cylinder remains same position when it reaches either end of stroke even if the input air source is gone.

■ Non lubrication

- Self-lubricating bush provides longer service life.

■ High quality long service life

- Stainless steel cylinder tubes for better corrosion resistance.

■ Magnetic as standard

Specification

Model	MCMBL	
Tube I.D. (mm)	32	40
Port size	Rc1/8	Rc1/4
Medium	Air	
Max. operating pressure	1 MPa	
Min. operating pressure	0.15 MPa	
Proof pressure	1.5 MPa	
Lubricator	Not required	
Ambient temperature	-5~+60°C (No freezing)	
Available speed range	50~750 mm/sec	
Max. allowable kinetic energy (J)	Cushion pad	0.29
	Cushion air	0.59
Lock unit backlash	2 mm or less	
Sensor switch	RDC, RQC  , RCM 	
Sensor switch band	R*C	BKC-1 (Not for R*CV angle cable)
	RCM	BM32
		BM40

■ Accessories & Connector

Accessories					
Code	LB (LB×2, with cover nut ×1)	NUT		CA	CB
Mounting Tube I.D.	 with nut	 Rod nut	 Cover nut		
ø32	LB-M2-25x2	NUT-M10x1.25x6Hx17B	NUT-M26x1.5x8Hx32B	CA-M2-25	CB-M2-25
ø40	LB-M2-40x2	NUT-M14x1.5x8Hx22B	NUT-M32x2.0x10Hx41B	CA-M2-40	CB-M2-40

	Accessories				Connector	
Code	FA	FB	TA	TB	Y	I
Mounting Tube I.D.						
ø32	FA-M2-25		TA-M2-25		Y-M2-25	I-M2-25
ø40	FA-M2-40		TA-M2-40		Y-Q1-40	I-M2-40

Pin

Applicable	Y&I connector	CA&CB accessories
Code	PIN-Y-P (with split pin / snap ring)	PIN-CB-P (with split pin / snap ring)
Fig Tube I.D.	 ø32 ø40	 ø32 ø40
ø32	PIN-M2-20-1-P	PIN-M2-20-1-P
ø40	PIN-M2-40-2-P	PIN-M2-40-1-P

■ Order example of self-assembled


The tube I.D. $\varnothing 32$ of LB accessories, Y connector and pin.

No.	Order number	Qty
1	LB-M2-25x2	1
2	Y-M2-25	1
3	PIN-M2-20-1-P	1

* To order accessories/
connectors/ pin separately,
please place orders separately
according to the order codes
in the above table.

■ Order example of factory assembled


⚠ Cylinders and accessories are distinguished by the symbol " + ".



END LOCK CYLINDER

Use recommended air pressure circuit

- The circuit layout must be settled properly. The recommended circuit design is shown below.




Precautions

- Do not use 3-way solenoid valves. The cylinder cannot be locked when compressed air is trapped in the lock side port. And the lock may be released due to the air leakage of solenoid valve, even it was locked successfully.
- Do not adjust or mount the cylinder when the lock is on.
- The operation load do not exceed 50% of the cylinder maximum output.
- Do not operate a workpiece with multiple end-lock cylinders simultaneously.
- Use an one-way speed control valve with meter-out circuit layout design. The lock cannot be released when the circuit layout is meter-in design.
- Operate the lock only when the cylinder is at the either end-position of stroke.
- The air supply must be higher than 0.15 MPa to operate the lock.
- The lock will be on when automatically when the pressure of the lock is lower than 0.1 MPa or less.
- There are many conditions that will cause the exhaust speed to reduce. The examples are shown below.
 - When the exhausting route length is too long.
 - When the one-way speed control valve is too far from cylinder port.
 - When the silencer of the solenoid valve is blocked or clogged.
- When the cushion needle is fully closed, the piston rod may not be able to reach the end of its stroke. When the cushion needle is fully closed and the cylinder is locked, the lock may not be able to be released.


Maintains the cylinder's original position even if the air supply is interrupted.

Prevention of dropping at the rising end

With rear lock




Locking of door With front lock



The replacement of rod sealing ring

- Remove the retaining ring.
- Take out the washer and clean it.
- Take out the rod sealing ring.
- Lubricate the new rod sealing ring and piston rod with grease.
- Put in the new rod sealing ring.
- Put in the washer.
- Install the retaining ring.

Please contact our sales department for purchasing grease.



END LOCK CYLINDER


Manual Lock Releasing

- 1 Install a bolt into the locking rod and pull it up by hands. When your hands release, the locking rod will move back by spring force and continue locking.

The bolt size, inner spring pulling force and the stroke of locking rod are listed below.


MODEL	Thread size	Pulling force	Stroke (mm)
MCMBL-32	M2.5×0.45×25 ℓ	4.9 N	2
MCMBL-40	M3×0.5×30 ℓ	10.0 N	3

- 2 The bolt must be uninstalled after manual lock releasing, or the weight of bolt may cause some performance problems of the lock.




Installation of sensor switch

Sensor switch: R*C
Band: BKC-1



Sensor switch: RCM
Band: BMG*




Code Tube I.D.	Sensor switch	Band	A	B	C	D	E
32	RDC, RQC	BKC-1	33	28	27	9	M3×6L
	RCM	BM32	28.3	27.6	28	9	M3×16L
40	RDC, RQC	BKC-1	37	34.5	27	9	M3×6L
	RCM	BM40	32.3	33.6	28	9	M3×16L


Working Principle

- Both front locking type and rear locking type have the same mechanism. The pictures below shows that how a rear locking type cylinder works.


- 1 When the air pressure is input from front cap, the piston will move backward. After the piston nears the end of the stroke, the slope of chamfered rod (the position of *mark) will touch the locking rod.




- 2 The locking rod will be guided with the slope and keeps moving upward.




- 3 The locking rod will be pushed into the locking slot of the piston rod by the spring force. At this time, the cylinder is locked.




- 4 When the air pressure is input from rear cap, the piston will start moving forward. At the same time, the locking rod will be pushed up by the compressed air and make the piston rod unlocked.



- 5 As the locking rod is no longer locking the piston rod, the cylinder can move forward.







Material

No.	Cushion		Part name	Material	Q'y
	Pad	Air			
1	●	●	Rod cover	Aluminum alloy	1
2	●	●	Head cover	Aluminum alloy	1
3	●	●	Tube	Stainless steel	1
4	●	●	Piston rod	Carbon steel	1
5	●	●	Piston-R	Aluminum alloy	1
6	●	●	Piston-H	Aluminum alloy	1
7	●	●	O-ring	NBR	1
8	●	●	Piston packing	NBR	1
9	●	●	Magnet ring	Magnet	1
10	●	●	Wear ring	Resin	1
11	●	●	Piston bolt	Carbon steel	1
12	●	●	Rod bush	Bearing alloy	1
13	●	●	Rod sealing ring	HNBR	1
14	●		Cushion gasket	NBR	2

No.	Cushion		Part name	Material	Q'y
	Pad	Air			
15	●	●	Cover nut	Carbon steel	1
16	●	●	Nut	Carbon steel	2
17	●	●	Retaining ring	Spring steel	1
18	●	●	Washer	Carbon steel	1
19	●	●	Lock piston	Carbon steel	1
20	●	●	Holder	Aluminum alloy	1
21	●	●	Piston packing	NBR	1
22	●	●	Spring	SWP	1
23	●	●	DU bush	—	2
24	●	●	Bolt	Carbon steel	2
25		●	Cushion ring	NBR	2
26		●	Cushion needle valve	Carbon steel	2
27		●	O-ring	NBR	2
28		●	Steel ball	Stainless steel	2



Code Tube I.D.	End lock	S		ZZ	
		Pad	Air	Pad	Air
32	R	64	75	122	133
	H	64	72	122	130
40	R	88	96	154	162
	H	88	93	154	159



Code Tube I.D.	A	B	AL	D	E	F	FL	G	H	H1	H2	I	K	MM	N	NA	NB	NN	P	P1	P2	Q
32	22	15	19.5	12	26	13	11.5	8	45	6	8	37.5	6.5	M10×1.25	15	34.5	44.8	M26×1.5	Rc1/8	10.3	M2.5×0.45	8
40	24	19	21	14	32	16	14.5	11	50	8	10	46.5	7	M14×1.5	21.5	42.5	54.8	M32×2.0	Rc1/4	12.3	M3×0.5	11.5