

# MVHB-220 series

## HAND LEVER VALVE



Mindman

### Specification

| Model                    | MVHB-220-4TV<br>MVHB-220-4TV-SP | MVHB-220-4TV*<br>MVHB-220-4TV*-SP |
|--------------------------|---------------------------------|-----------------------------------|
| Bore No. (Port size)     | 8A (1/4)                        |                                   |
| No. of port              | 5                               |                                   |
| No. of position          | 2                               | 3                                 |
| Medium                   | Air                             |                                   |
| Operating pressure range | 0~0.8 MPa                       |                                   |
| Effective orifice        | 18 mm <sup>2</sup>              | 16 mm <sup>2</sup>                |
| Ambient temperature      | -5~+60°C (No freezing)          |                                   |
| Weight                   | 193 g                           | 234 g                             |



Technical data



Caution for safety  
(Read before installing)



### Order example

MVHB - 220 - 4TVC - SP - M - □ - G

MODEL

BODY  
WIDTH

4: 4way (5 port)

VALVE  
TYPE

Blank: 5/2  
C: Closed center (5/3)  
P: Pressure center (5/3)  
R: Exhaust center (5/3)

SPRING  
RETURN

DUST COVER  
MATERIAL

Blank: NBR  
E: EPDM

Blank: Standard type  
M: Panel mounting

PORT THREAD

Blank: Rc thread  
G: G thread  
NPT: NPT thread

\*1. NBR: Good oil resistance and abrasion resistance, not suitable for using in polar solvents.

EPDM: Excellent water resistance and chemical resistance, not suitable for using oil place.

\*2. Suitability of material

### Panel mounting style

